

INJECTORS

ANS-62 / ANS-108 INJECTOR



| Technical data | | ANS 62 | ANS 108 |
|-------------------------------------------------------------------------------------|--------|--------------------|---------------------|
| Number of needle sockets | [pcs.] | 62 | 108 |
| Total number of needles | [pcs.] | 62/124/248 | 108/216/432 |
| Capacity | [kg/h] | ~3500 | ~4500 |
| Conveyor width | [mm] | 400 | 500 |
| Clearance (needle lift height) | [mm] | | 250 |
| Brine pressure | [bar] | | 0,5-4 |
| Total power | [kW] | | 7,5 |
| Power supply | [V/Hz] | | 3x400/50 |
| Required compressed air supply | [bar] | | min.6 |
| (LxBxH) dimensions | [mm] | ~1900 x 900 x 2200 | ~2200 x 1000 x 2200 |
| Weight | [kg] | ~800 | ~1000 |
| OPTIONAL - brine gap-filter adapted to work with the injector | | | |
| OPTIONAL - adaptation to the injection of fish fillets | | | |
| OPTIONAL - twin needles, quadruple needles, different thicknesses - 4mm / 3mm / 2mm | | | |

THE MOST CURRENT DATA ABOUT OUR PRODUCT IS AVAILABLE HERE:

